BUILDING TRUST

PRODUCT DATA SHEET

Sika® Remover-208

Solvent-based cleaning agent for strongly contaminated non-porous surfaces

TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)

Chemical base	Solvent-based
Color (CQP001-1)	Colorless, clear
Application temperature	5 – 40 °C
Application method	Wipe-on, wipe-off with lint-free paper towel
Shelf life	24 months [A]

CQP = Corporate Quality Procedure [A] stored in sealed container in up-right position in a dry place at ≤ 25 °C

DESCRIPTION

Sika® Remover-208 is a solvent-based colorless clear cleaning agent for painted substrates. It is also used to remove traces of Sikaflex® products.

PRODUCT BENEFITS

- Removes heavy contaminats
- Suitable for most painted surfaces and plastics
- Available in aerosol can

AREAS OF APPLICATION

Sika® Remover-208 is used to pre-clean strongly contaminated non-porous substrates. Sika® Remover-208 can be used to clean painted surfaces prior to bonding.

Sika® Remover-208 can also be used to remove uncured excess of Sikaflex® adhesive or sealant from application tools or soiled surfaces.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

METHOD OF APPLICATION

Removal of uncured material

Remove the bulk of the Sikaflex® residue with a knife or spatula. Moisten a rag or towel with Sika® Remover-208 and wipe off the remaining adhesive or sealant.

Surface Cleaning

Wipe painted surfaces with a moistened rag or towel with Sika® Remover-208. Wet the paper towel with solvent by pouring the liquid onto the cloth. Never dip the paper towel into the Sika® Remover-208 as it may contaminate it! Wipe the surface with the wetted paper towel. Use fresh paper towels regularly in order to retain the cleansing power.
Before the solvent dries on the surface (evaporates), wipe it off with a clean, dry, lint-free paper towel.
Repeat the last two steps until no contaminants show up on a white paper towel.
Do not use on sensitive surfaces such as fresh paints.
Tightly reseal container immediately after each use.

IMPORTANT NOTE

Compatibility with the actual substrate is to be verified prior the application.
Discard any Sika® Remover-208 that looses its clear appearance (contaminated).

FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.
Copies of the following publications are available on request:

- Safety Data Sheets

PACKAGING INFORMATION

Spray	400 ml
Can	1000 ml
Bucket	5 l
Pail	20 l 50 l

BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

DISCLAIMER

The information, and, in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika (Singapore) Pte Ltd.
28 Tuas South Ave 8
Singapore 637648
Phone: +65 6861 0632
Fax: +65 6862 3915
Email: sales@sg.sika.com
www.sika.com.sg