

# Sikasil® WS-300 EU

## DECLARATION OF PERFORMANCE

## No. 45505808

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	45505808
2	INTENDED USE/S	Sealants for facade for exterior and interior application F EXT-INT CC
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-1:2012
	Notified body/ies:	1119

### 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD	System 3	
Resistance to flow	≤ 3 mm	System 3	
Loss of volume	≤ 10 %	System 3	
Tensile properties (i.e. elongation) at maintained extension after water immersion (elastic)	NF at 100 % Elongation	System 3	
Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)	≤ 0.9 MPa at 100 % Elongation	System 3	EN 15651- 1:2012
Tensile properties (i.e. at maintained elongation) for non-structural sealants used in joints in cold climate areas (-30°)	NF at 100 % Elongation	System 3	
Durability	Pass	System 3	

## 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Tomasz Gutowski

Function: Corporate Standardization

and Approvals

At Warsaw on 30 March 2018

Name: Tatiana Ageyeva

Function: Standardization and Approvals

At Warsaw on 30 March 2018

End of information as required by Regulation (EU) No 305/2011



### **RELATED DECLARATION OF PERFORMANCE**

Product Name	Harmonised technical specification	DoP Number
Sikasil® WS-300 EU	EN 15651-2:2012	98574253

Sikasil® WS-300 EU 45505808 2018.03 , ver. 2

**Declaration of Performance** 

1329





18

Sika Services AG, Zurich, Switzerland

DoP No. 45505808

EN 15651-1:2012

Notified Body 1119

Sealants for facade for exterior and interior application

F EXT-INT CC

Reaction to fire Class E
Resistance to flow  $\leq 3 \text{ mm}$ Loss of volume  $\leq 10 \%$ 

Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)

≤ 0.9 MPa at 100 % Elongation

http://dop.sika.com

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

#### **LEGAL NOTE**

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Declaration of Performance** 

Sikasil® WS-300 EU 45505808 2018.03 , ver. 2 1329



Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland www.sika.com

**Declaration of Performance** Sikasil® WS-300 EU

45505808 2018.03 , ver. 2

1329

