

## MATERIĀLA APRAKSTS

# Sika® Aktivator-100

Transparent solvent-based adhesion promoter for various substrates

**RAKSTURĪGIE PRODUKTA DATI (CITAS VĒRTĪBAS SKATĪT DROŠĪBAS DATU LAPĀ)**

<b>Kīmiskā bāze</b>	Solvent-based adhesion promoter		
<b>Krāsa (CQP001-1)</b>	Bezkrāsains līdz viegli dzeltenīgs		
<b>Iestrādes temperatūra</b>	5 – 40 °C		
<b>Iestrādes metode</b>	Wipe-on, wipe-off with lint-free paper towel		
<b>Pārklājums</b>	20 ml/m <sup>2</sup>		
<b>Nozūšanas laiks</b>	≥ 15 °C	10 minutes <sup>A</sup>	
	< 15 °C	30 minutes <sup>A</sup>	
	maximum	2 hours <sup>A</sup>	
<b>Uzglabāšanas ilgums</b>	12 mēneši <sup>B</sup>		

CQP = Corporate Quality Procedure

<sup>A</sup>) for specific application, temperature and flash-off time may be different<sup>B</sup>) stored in sealed container in a dry place at ≤ 25 °C**APRAKSTS**

Sika® Aktivator-100 is a solvent-based colorless adhesion promoter, which reacts with moisture and deposits active groups on the substrate. These groups act as a link between substrates and primers or sealants/adhesives. Sika® Aktivator-100 is specifically formulated for the treatment of bond faces prior to application of Sika's elastic adhesives and sealants.

**PRODUKTA PRIEKŠROCĪBAS**

- Easy to use
- Enhanced adhesion on a wide variety of non-porous substrates
- Short flash-off time
- Transparent

**IZMANTOŠANAS JOMAS**

Sika® Aktivator-100 is used to improve adhesion on substrates such as float glass, ceramic screen prints, the cut face of old Polyurethane adhesives and paints. After intensive testing, this activator is also suitable to enhance the adhesion of other Sika sealants and adhesives on non-porous substrates.

Seek manufacturer's advice and perform tests on original substrates before using Sika® Aktivator-100 on materials prone to stress cracking.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed to ensure adhesion and material compatibility.

**MATERIĀLA APRAKSTS**

Sika® Aktivator-100

Versija 05.01 (08 - 2024), lv\_LV  
014560011000001000

## IESTRĀDES METODE

Surfaces must be clean, dry and free from grease, oil, dust and contaminants. Adhesion on substrates may be improved by adding and/or combining pre-treatment processes such as scuffing and cleaning prior the activator application.

## Iestrāde

Wipe bond faces with a clean, lint-free paper towel moistened (not wet) with Sika® Aktivator-100. Immediately wipe-off with a clean, dry, lint-free paper towel. Never dip the towel into the activator. Only wipe the surface with a clean side of the towel. Do not moisten the same paper towel twice and change it frequently.

Sika® Aktivator-100 has to be applied sparingly as excess of activator could lead to adhesion failure.

If the pre-treated area is not bonded within the maximum flash-off time, the activation process has to be repeated (once only).

Ideal application and surface temperature is between 15 °C and 25 °C.

Consumption and method of application depends on the specific nature of the substrates.

Tightly reseal container immediately after each use.

Pad: Hold pad directly against the frit on the glass, then pinch the handle with thumb and index finger to break internal vials thus releasing Sika® Aktivator-100 into the pad (do not bend!).




Fig. 1: Sika® Aktivator-100 Pad

## MATERIĀLA APRAKSTS

Sika® Aktivator-100

Versija 05.01 (08 - 2024), lv\_LV  
014560011000001000

## Sika Baltic SIA

Piedrujas iela 7 k-5  
LV-1073 Riga, Latvija  
Tālrunis: +371 20369997  
[www.sika.lv](http://www.sika.lv)

## SVARĪGA PIEZĪME

Sika® Aktivator-100 contains solvent which may dull the surface finish of some freshly applied paints. Preliminary trials must be carried out.

Never apply to porous substrates since it may not dry completely and prevent the adhesive or sealant from curing.

Protect adjacent surfaces by masking where necessary.

Sika® Aktivator-100 is a moisture reactive system. In order to maintain product quality it is important to reseal the container with the inner plastic liner immediately after use. Once the surface pre-treatment operation is completed the cap has to be screwed on. Prolonged exposure to atmospheric moisture will cause Sika® Aktivator-100 to become inactive. Immediately discard Sika® Aktivator-100 if it has become opaque instead of clear. Dispose of product approx. one month after opening if used frequently or after two months in case of infrequent use. 30 ml cans and pads are for single application only.

Never dilute or mix Sika® Aktivator-100 with any other substances.

It must not be used for tooling/smoothing of products or as cleaning agent.

If used on transparent or translucent substrates such as float glass, plastics, etc., an adequate UV protection is mandatory except for Sikasil® silicone sealants and adhesives.

## PAPILDINFORMĀCIJA

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Working instructions issued for a defined application may further specify technical data contained in this Product Data Sheet.

Copies of the following publications are available on request:

- Safety Data Sheets

## INFORMĀCIJA PAR IEPAKOJUMU

	30 ml
Pudele	250 ml
	1000 ml

Aplikators	3,3 ml
------------	--------

## MATERIĀLA DATU PAMATOJUMS

Visi šajā dokumentā paziņotie tehniskie dati iegūti uz laboratorisku izmēģinājumu pamata. Faktiski izmērītās vērtības var būt atšķirīgas to faktoru dēļ, kurus mēs nevaram ietekmēt.

## VESELĪBAS AIZSARDZĪBAS UN DROŠĪBAS INFORMĀCIJA

Lai iegūtu informāciju un padomus par drošu apiešanos ar produktu, tā uzglabāšanu un deponēšanu lietotājam jāizmanto produkta jaunākā Drošības datu lapa, kas satur fizikālo, ekoloģisko, toksikoloģisko un citu uz drošību attiecošos informāciju.

## SAISTĪBU ATRUNA

Visa informācija, un, it īpaši - ieteikumi, kas attiecas uz firmas Sika materiālu pielietojumu un galīgo patēriņu, ir uzticama un balstīta uz firmas Sika pašreizējo pieredzi un zināšanām par materiāliem, - ar nosacījumu, ka uzglabāšana un rīkošanās ar tiem norit pareizi, un to uzklāšana norit normālos apstākļos saskaņā ar Sika rekomendācijām. Praksē pierādījies, ka materiālu, pamatslānu un attiecīgās darbu veikšanas vietu stāvokli ir tik atšķirīgi, ka no šīs informācijas, ciemī rakstiskiem ieteikumiem vai piedāvātās konsultācijas vadoties, neizriet nekādas garantijas, neatkarīgi no piedāvājuma vai piemērotības attiecīgajam nolūkam, kā arī – no jebkādām tiesiskajām attiecībām izrietoša atbildība par zaudējumiem. Materiāla lietotājam ir jāpārbauda materiāla piemērotība paredzētajam pielietojumam un mērķim. Sika patur tiesības mainīt savu izstrādājumu īpašības. Ir jāievēro trešo pušu patētu tiesības. Visi pasūtījumi tiek pieņemti pēc pašreizējiem pārdošanas un piegādes nosacījumiem. Lietotājiem vienmēr ir jāatsaucas uz jaunāko attiecīgā produkta Materiāla aprakstu, kura kopijas tiek piegādātas pēc pieprasījuma.

