

BUILDING TRUST

PRODUCT DATA SHEET Sika[®] Mixer Cleaner

Cleaning agent for silicone metering and mixing equipments

TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)

Chemical base	High-boiling organic solvent with active ingredient
Color	Brown
Density	0.87 kg/l
Application temperature	5 – 40 °C
Application method	Immersion or purging
Shelf life	24 months

CQP = Corporate Quality Procedure

DESCRIPTION

Sika® Mixer Cleaner is a cleaning liquid that • Increases the mixer lifetime can dissolve uncured and cured silicone sealant and adhesive in equipment hoses and • Dissolves cured silicone sealant or adhesive mixers.

PRODUCT BENEFITS

- Cleans cured mixer

AREAS OF APPLICATION

Sika® Mixer Cleaner can be used to clean mixer and single machine parts from 1- and 2component silicone sealants and adhesives. This product is to be used by professional experienced users only. Trials must be carried out prior to use.

METHOD OF APPLICATION

Parts to be cleaned should be immersed in Sika® Mixer Cleaner for several hours depending on the degree of vulcanization and thickness of the layer of silicone sealant. The instructions provided in the Safety Data Sheet must be obeyed. Afterwards remaining silicone residues may be easily removed mechanically.

Alternatively, Sika[®] Mixer Cleaner may be applied in standard commercially available cleaning pumps that are offered for silicone metering and mixing equipment. The static mixer is rinsed with Sika[®] Mixer Cleaner for several hours, depending on the degree of contamination.

IMPORTANT NOTE

Before immersed parts are used again, they must be completely cleaned and dried.

If using a purging pump the production may only be continued after Sika® Mixer Cleaner was completely removed form the cleaned static mixer.

Keep Sika[®] Mixer Cleaner containers closed when not in use. Tightly reseal container immediately after each use.

STORAGE CONDITIONS

Store Sika[®] Mixer Cleaner in the sealed container in a cool dry place.

FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

Safety Data Sheets

PACKAGING INFORMATION

Pail	23 kg
Drum	160 kg

BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

DISCLAIMER

The information, and, in particular, the recommendations relating to the application and enduse of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PRODUCT DATA SHEET Sika® Mixer Cleaner Version 02.01 (03 - 2023), en_ZA 014362000019003000 Sika South Africa (Pty) Ltd 9 Hocking Place, Westmead, 3608 South Africa Phone +27 31 792 6500 www.sika.co.za



