
Sikasil® WS-290 EU

DECLARATION OF PERFORMANCE

No. 35170648

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	35170648
2	INTENDED USE/S	Sealants for exterior and interior application F EXT-INT
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-1:2012
	Notified body/ies:	1119

Declaration of Performance

Sikasil® WS-290 EU

35170648

2019.12 , ver. 2

1104

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	Class E	System 3	
Release of chemicals dangerous to the environment and health	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3	EN 15651-1:2012
Loss of volume	≤ 10 %	System 3	
Tensile properties at maintained extension after water immersion (elastic)	NF at 100 % elongation	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization and Approvals
At Warsaw on 02 December 2019

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 02 December 2019



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikasil® WS-290 EU	EN 15651-2:2012	80787187

Declaration of Performance

Sikasil® WS-290 EU
35170648
2019.12 , ver. 2
1024



19

Sika Services AG, Zurich, Switzerland

35170648

EN 15651-1:2012

Notified Body 1119

Sealants for exterior and interior application F EXT-INT

Reaction to fire	Class E
Water tightness and air tightness	
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10 %

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

Sikasil® WS-290 EU

35170648

2019.12 , ver. 2

1024

3/4

BUILDING TRUST



Sika Services AG
Tüffenwies 16
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
Sikasil® WS-290 EU
35170648
2019.12 , ver. 2
1024

4/4

BUILDING TRUST

