

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:  
**MEDB000019S**  
Revision No:  
**2**

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

## This is to certify:

**That the Surface materials and floor coverings with low flame-spread characteristics: Adhesives used in the construction of "A", "B" & "C" class divisions**

with type designation(s)  
**SikaForce®-141 CT18**

Issued to  
**Sika Services AG**  
**Zürich, ZH, Switzerland**

is found to comply with the requirements in the following Regulations/Standards:  
Regulation (EU) 2020/1170,  
item No. MED/3.18e. SOLAS 74, Reg. II-2/3, II-2/5, II-2/9 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-08-08**.

Issued at **Hamburg** on **2021-08-09**

DNV local station:  
**Augsburg**

Approval Engineer:  
**Timo Linn**



Notified Body  
No.: **0098**

for **DNV SE**

**Christine Mydlak-Roeder**  
**Head of Notified Body**

The mark of conformity may only be affixed to the above type approved equipment and a Manufacturer's Declaration of Conformity issued when the production-surveillance module (D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU. This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



### Product description

“SikaForce®-141 CT18” is a polyurethane adhesive used for sandwich panel bonding.

Colour: brown

Applied maximum amount of wet adhesive: 150 g/m<sup>2</sup>

### Application/Limitation

Approved for use as adhesive with low flame spread characteristics.

Maximum gross calorific value shall be documented separately where applicable, ref. SOLAS Chapter II-2 Reg. 5.3.

Each product is to be supplied with its manual for application and use.

### Type Examination documentation

Test report no. PFB10206A dated 2016-03-16 issued by the Danish Institute of Fire and Security Technology (DBI), Hvidovre, Denmark.

Manufacturers’s product data sheet SikaForce®-7141 L18 Version 2 (02/12)

### Tests carried out

Tested according to IMO Res. MSC.307(88) - 2010 FTP Code, Annex 1, Part 5

### Marking of product

The product or packing is to be marked with name and address of manufacturer, type designation and MED Mark of Conformity (see first page).

### Marking of product

The product or packing is to be marked with:

- name and address of manufacturer,
- type designation,
- fire technical rating and
- the MED Mark of Conformity (see page 1) and USCG approval number, if applicable.