



# Sikafloor<sup>®</sup> Marine VEM

## VISCO-ELASTIC VIBRATION DAMPING MORTAR

- Remarkable vibration damping
- Isocyanate-free
- Great pumpability

BUILDING TRUST



# Sikafloor® Marine VEM

## VISCO-ELASTIC VIBRATION DAMPING MORTAR

Sikafloor® Marine VEM is a one-component visco-elastic mortar based on polymer modified cement and is used as a vibration damping system. It is applied on interior decks in combination with Sikafloor® Marine-18 as well as with Sikafloor® Marine-118 FC.

For specific applications consult the product data sheet or Sika technical service.

### PRODUCT BENEFITS

- Great vibration damping factor
- Excellent visco-elastic effect
- Extremely environment-friendly

### Technical Properties

Chemical base	1-Component polymer
Density	1.3 kg/m <sup>2</sup> /mm
Applied thickness	1 – 2 mm
Ready to walk on	8 – 12 hr.
Elongation at break	55%
Tensile strength	0.6 N/mm <sup>2</sup>
Shore A	75
Shelf life	12 months

Our most current General Sales Conditions shall apply. Please consult the most current local Product Data Sheet prior to any use.



**SIKA SERVICES AG**  
Tueffenwies 16  
8048 Zurich  
Switzerland

**Contact**  
Phone: +41 58 436 40 40  
Fax: +41 58 436 55 30  
[www.sika.com/marine](http://www.sika.com/marine)

**BUILDING TRUST**

