
SikaMembran® Eco Out

DECLARATION OF PERFORMANCE

No. 48566670

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	48566670
2	INTENDED USE/S	Flexible sheets of rubber intended for use as water vapor control layers for buildings
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3 System 4
6a	HARMONISED STANDARD:	EN 13984:2013
	Notified body/ies:	0767, 1213

Declaration of Performance

SikaMembran® Eco Out

48566670

2021.03 , ver. 2

1107

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Water tightness	NPD	System 3	EN 13984:2013
Resistance to impact	NPD	System 4	
Durability - Water vapor resistance after artificial ageing	NPD	System 4	
Durability - Chemical resistance	NPD	System 4	
Tear resistance - md/cmd	≥ 35 N	System 4	
Joint strength	≥ 50 N/50 mm	System 4	
Water vapor resistance	μ = 4 000	System 3	
Tensile properties:			
Maximum tensile force - md/cmd	≥ 5 N/mm ²	System 4	
Elongation - md/cmd	> 300 %	System 4	
Reaction to fire	Class E	System 3	
Dangerous substances	NPD	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Tomasz Gutowski
Function: Corporate Standardization and Approvals
At Warsaw on 18 March 2021

Name : Tatiana Ageyeva
Function: Standardization and Approvals
At Warsaw on 18 March 2021



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

SikaMembran® Eco Out
48566670
2021.03 , ver. 2
1107



21

Sika Services AG, Zurich, Switzerland

48566670

EN 13984:2013

Notified Body 0767, 1213

Flexible sheets of rubber intended for use as water vapor control layers for buildings

Tear resistance - md/cmd	≥ 35 N
Joint strength	≥ 50 N/50 mm
Water vapor resistance	$\mu = 4\ 000$
Tensile properties:	
Maximum tensile force - md/cmd	≥ 5 N/mm ²
Elongation - md/cmd	> 300 %
Reaction to fire	Class E

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Declaration of Performance

SikaMembran® Eco Out

48566670

2021.03 , ver. 2

1107

3/4

BUILDING TRUST



Sika Services AG
Tüffenwies 16-22
8064 Zürich
Switzerland
www.sika.com

Declaration of Performance
SikaMembran® Eco Out
48566670
2021.03 , ver. 2
1107

4/4

BUILDING TRUST

